

GMOIL

KOMPRESSOR OIL K-19



MEETS REQUIREMENTS:
DIN 51506-VDL

Synaglar / Исследования / Checks	Synag usuly/ Метод / Method	Görkezileri / Показатели / Indicators
Kinematik şeþbeşlikligi 100°C-da mm2/s, çäklerde Кинематическая вязкость при 100°C мм²/с, в пределах Kinematic viscosity at 100°C mm²/s, within	TDS 33 ASTM D445	17-21
Sepbeşliklilik indeksi, az däl Индекс вязкости, не менее Viscosity index, not less than	TDS 25371 ASTM D2270	120
Doňma temperaturasy °C, ýokary däl Температура застывания °C, не выше Pour point °C, not higher	TDS 966 ASTM D97	-15
Ýalpyldama temperaturasy °C, pes däl Температура вспышки °C, не ниже Flash point °C, no less than	TDS 4333 ASTM D92	245

© "Geljege Miras" hususy kärhanasy

Önümçiliğin salgysy: Türkmenistan, Ahal welayaty, Ak bıggıday etraby,
Türkmenistanyň Senaǵatçylar we telekeçler birligmesiniň senagat zolagy, 16 njiýer bölegi.

+993 12 414029

gelejgeomiras.com.tm

gelejgeomiras@mail.ru



TDS 1110-2018



20L

208L